

GOBLE

Serial No. 10/036,500

AMENDMENTS TO THE CLAIMS

1. (Withdrawn)
2. (Withdrawn)
3. (Withdrawn)
4. (Withdrawn)
5. (Withdrawn)
6. (Withdrawn)
7. (Withdrawn)
8. (Withdrawn)
9. (Withdrawn)
10. (Withdrawn)
11. (Withdrawn)
12. (Withdrawn)
13. (Withdrawn)
14. (Withdrawn)
15. (Withdrawn)
16. (Withdrawn)
17. (Withdrawn)
18. (Withdrawn)
19. (Withdrawn)
20. (Withdrawn)

GOBLE

Serial No. 10/036,500

21. (Withdrawn)

22. (Withdrawn)

23. (Withdrawn)

24. (Withdrawn)

25. (Withdrawn)

26. (Withdrawn)

27. (Withdrawn)

28. (Withdrawn)

29. (Withdrawn)

30. (Withdrawn)

31. (Canceled)

32. (Canceled)

33. (Canceled)

34. (Canceled)

35. (Canceled)

36. (Canceled)

37. (Previously Presented) A method of treating a tumour in a colon using an electrosurgical system comprising:

an electrosurgical generator adapted to generate a radio frequency oscillating voltage output across first and second output terminals;

an electrosurgical instrument having an active tissue treatment electrode

GOBLE

Serial No. 10/036,500

connected to the first generator output terminal;

fluid delivery means for delivering electrically-conductive fluid to the tumour to be treated; and

a return electrode connected to the second generator output terminal,

the method comprising the steps of:

enclosing, in a substantially fluid-tight manner, a space in the colon within which the tumour to be treated is located, and within which at least the active electrode is located;

operating the fluid delivery means at least partly to fill the space with electrically-conductive fluid;

operating the generator to apply a radio frequency voltage between the active and return electrodes, and completing at least a part of a conduction path between the active and return electrodes using the electrically-conductive fluid; and

manipulating the active electrode in the vicinity of the tumour to be treated;

wherein the space is enclosed by means of a flexible enclosing member which forms a seal with a portion of the colon.

38. (Original) A method according to claim 37, wherein the method further comprises the step of reducing the pressure within the space to a level below air pressure in the immediate vicinity outside the space.

39. (Previously presented) A method of treating a tumour in a colon using an

GOBLE

Serial No. 10/036,500

electrosurgical system comprising:

an electrosurgical generator adapted to generate a radio frequency oscillating voltage output across first and second output terminals;

an electrosurgical instrument having an active tissue treatment electrode connected to the first generator output terminal;

fluid delivery means for delivering electrically-conductive fluid to the tumour to be treated; and

a return electrode connected to the second generator output terminal,

the method comprising the steps of:

enclosing, in a substantially fluid-tight manner, a space in the colon within which the tumour to be treated is located, and within which at least the active electrode is located;

operating the fluid delivery means at least partly to fill the space with electrically-conductive fluid;

operating the generator to apply a radio frequency voltage between the active and return electrodes, and completing at least a part of a conduction path between the active and return electrodes using the electrically-conductive fluid; and

manipulating the active electrode in the vicinity of the tumour to be treated;

wherein the space is enclosed by means of a flexible enclosing member which forms a seal with a portion of the colon; and

GOBLE

Serial No. 10/036,500

wherein the flexible enclosing member includes a proximal bung and a distal bung.

40. (Original) A method according to claim 39, including the further step of inflating the colon by delivering conductive fluid to the space through a first opening in the distal bung so that the tumour can be treated by the active electrode.

41. (Original) A method according to claim 40, including the further step of inserting into the space through the first opening an endoscope having a first channel for delivering the conductive fluid and a second channel for inserting the active electrode.

42. (Original) A method according to claim 40, including the further step of removing the conductive fluid from the space through a second opening in the proximal bung.

43. (Original) A method according to claim 37, wherein the flexible enclosing member is inserted endoscopically into the space through the colon's lumen.

44. (Previously presented) A method of treating a tumour in a colon using an electrosurgical system comprising:

an electrosurgical generator adapted to generate a radio frequency oscillating

GOBLE

Serial No. 10/036,500

voltage output across first and second output terminals;

an electrosurgical instrument having an active tissue treatment electrode connected to the first generator output terminal;

fluid delivery means for delivering electrically-conductive fluid to the tumour to be treated; and

a return electrode connected to the second generator output terminal,

the method comprising the steps of:

enclosing, in a substantially fluid-tight manner, a space in the colon within which the tumour to be treated is located, and within which at least the active electrode is located;

operating the fluid delivery means at least partly to fill the space with electrically-conductive fluid, the space being enclosed by means of a flexible enclosing member which forms a seal with a portion of the colon;

operating the generator to apply a radio frequency voltage between the active and return electrodes, and completing at least a part of a conduction path between the active and return electrodes using the electrically-conductive fluid; and

manipulating the active electrode in the vicinity of the tumour to be treated; and

laparoscopically inserting a flexible sleeve to thereby surround a region of the colon containing the tumour to be treated and apply a second pressure against a first pressure resulting from the filling of the space with the electrically-conductive fluid.

GOBLE

Serial No. 10/036,500

45. (Original) A method according to claim 44, wherein the flexible enclosing member includes a proximal bung and a distal bung and wherein the proximal and distal bungs form a pressure seal against both the colon and the pressure applied via the inflatable sleeve.

46. (Original) A method according to claim 44, wherein the active electrode is manipulated to remove the tumour and a region of the colon within which the tumour is located once the blood supply and lymphatics of the region have been disconnected.

47. (Original) A method according to claim 40, including the further step of inserting into the space through the first opening an endoscope having a fluid channel for delivering the conductive fluid and an instrument channel for inserting the active electrode.